



CITY SQUARES

CARPET TILE

PRODUCT SPECIFICATIONS

STYLE NAME	City Squares
PRODUCT TYPE	Carpet Tile
CONSTRUCTION	Multi-Level Pattern Loop
FIBER	PP (Polypropylene)
DYE METHOD	Solution Dyed
PRIMARY BACKING	Synthetic
SECONDARY BACKING	Ultra-Flex Backing
PRODUCT SIZE	20" x 20"
SY PER CARTON	6.57 sy
PIECES PER CARTON	22
GAUGE	1/12
STITCHES	12/in
AVERAGE DENSITY	4900
TOTAL THICKNESS	0.239 in
OVERALL WEIGHT	120 oz./sy
WARRANTY	15 Year Commercial Limited Warranty with Stain and Color

PERFORMANCE TESTING

PILL TEST	Pass
RADIANT PANEL	Class 1 / ASTM E648
NBS SMOKE	Less than 450 / ASTM E662
ELECTROSTATIC PROPENSITY	Less than 3.5 kv / AATCC-134
CRI® GREENLABEL PLUS	GLP8233
ADA COMPLIANCE	>0.6, meets recommended static coefficient of friction for ADA walking surfaces

AVAILABLE COLORS

7971 Portland	7608 Madison	7720 Denver
7518 Albany	7785 Topeka	7737 Austin

Color samples available upon request. Actual colors may vary slightly from printed representations.

RECOMMENDED INSTALLATION METHODS

Quarter Turn	Ashlar	Brick	Random
--------------	--------	-------	--------

Ultra-Flex Backing allows for both glue-down and loose-lay installation methods. Follow CRI 104 Standard Guidelines for Installation of Commercial Carpet. Acclimate tiles to room temperature (65°F–95°F) for 24 hours prior to installation.

AFC SPECIFICATION NOTE: City Squares Carpet Tile is the AFC-specified product for multi-family corridors, common areas, and hospitality applications. Pair with Allstate Rubber Wall Base for a complete, code-compliant installation. Available through AFC's Spec & Estimate Engine — upload your floor plan at www.advancedflooringc.com for a full takeoff and material quote.